SPLIT SEAM TUBING

SPLIT BUTTSEAM	OD	WALLTHICKNESS
ROUND	3/16"	.012" to .016"
	7/32"	.009" to .025"
	1/4"	.009" to .030"
	5/16"	.009" to .030"
	3/8"	.009" to .036"
	7/16"	.009" to .036"
	9/16"	.009" to .036"
	1/2"	.015" to .060"
	5/8"	.020" to .060"
	3/4"	.020" to .060"
	7/8"	.020" to .060"
	1"	.020" to .070"
	1 1/8"	.020" to .060"
	1 1/4"	.015" to .040"
	1 5/16"	.048" to .090"
	1 1/2"	.020" to .060"
SQUARE	43/64"	.020" to .028"
	7/8"	.020" to .060"
	1"	.020" to .060"
RECTANGULAR	See open seam tubing category chart	

Materials: Unfinished and Prefinished Steel, Stainless, Aluminum, Brass, Alloys Copper, Bronze, Tempered, Clad, Perforated, Wire Cloth, Textured.

Prefinishes: Prepainted, Galvanized, Preplated, Prepolished, Prelacquered, Pre-Embossed, Pre-Laminated Vinyl, Preanodized, Aluminized, Galvannealled, Strippable-PVC Covered.

* Parts Cut to Length, with Clean Cut or Dimple Cut, Inline.

* Inline Press Fabrications: Holes, Slots, Cutouts, Dimples, End Fabricating, Flattened Ends.

* Secondary Fabricating: Does not lend itself to bending as seam is not joined, and will open.

* Telescoping Available

* Other Custom Special Shapes are possible, along with Finned, Flanged and Hemmed Seams

* Thicker Wall Thicknesses can be provided with Special Tooling

* Strippable-PVC Coating is Available for Protecting Decorative Finishes.

* Insertions and Tape Applicating can be done Inline.